

# RELATIVISTIC LASER INTERACTIONS WITH PREFORMED PLASMA CHANNELS AND GAMMA-RAY MEASUREMENTS

L.A.Gizzi, M.Galimberti\*, A.Giulietti, D.Giulietti\*, P. Tomassini  
*Intense Laser Irradiation Laboratory - IFAM, Area della Ricerca - CNR, Pisa (Italy)*  
*\*Also at Dipartimento di Fisica, Universit di Pisa and INFN, Pisa, Italy*

M. Borghesi

*Department of Pure and Applied Physics, The Queen's University, Belfast BT7 INN, UK*

D.H. Campbell, A. Schiavi, O. Willi

*Imperial College of Science, Technology and Medicine, SW7 2BZ, London, UK.*

## ABSTRACT

The propagation of a 1 ps laser pulse at intensities exceeding  $10^{19}$  Wcm<sup>-2</sup> in a low density plasma channel was experimentally tested. The channel was produced by a lower intensity previous pulse of the same duration. Plasma electrons were accelerated during the propagation of the main pulse, and high energy gamma ray detectors were used to detect their bremsstrahlung emission. The gamma-ray yield was studied for different channel conditions, by varying the delay between the channel forming pulse and the high intensity pulse. These results are correlated with the interferograms of the propagation region into the plasma.

Keywords: : laser-plasmas, relativistic interactions, electron acceleration

## 1. INTRODUCTION

The advent of the lasers in chirped pulse amplification (CPA) mode allowed for the first time the interaction of ultra-short radiation pulses with plasmas at relativistic intensities. The very large electric fields of such pulses can accelerate, directly or via induced perturbations of the electron density, charged particles [Ledingham *et al.* 2000; Cowan *et al.* 2000; Krushelnick *et al.* 1999; Borghesi *et al.* 1999; Gremillet *et al.* 1999, Pukhov *et al.* 1999]. Depending on the plasma density, several mechanisms can be activated which accelerate electrons to much higher energies than those due to the laser ponderomotive potential. Stimulated Raman forward scattering (SRFS) and self-modulated laser wake-field acceleration (SMLWFA) are some of the mechanisms proposed to explain the generation of a large number of >10 MeV electrons in recent experiments [Borghesi *et al.* 1999, Gremillet *et al.* 1999, Pukhov *et al.* 1999, Tzeng *et al.* 1997, Esarey *et al.* 1998, Tajima & Dawson 1979, Amiranoff *et al.* 1998]. Theoretical studies also predict that energy conversion into energetic electrons should be favoured when the laser pulse propagates in a cavitated structure such as a plasma channel. These issues may have important consequences on laser-driven plasma-based accelerators as well as on inertial fusion energy (IFE), particularly in the Fast Ignitor (FI) scheme. A major problem of laser-driven plasma-based accelerators is the short acceleration distance which is basically limited by laser beam diffraction [Leemans *et al.* 1998]. Propagation in a plasma channel has been proposed as a way of overcoming this limitation. It is well established that channels can be produced [Borghesi *et al.* 1997, Malka *et al.* 1997] as a result of laser interaction with underdense plasmas. Several experiments [Krushelnick *et al.* 1997, Mackinnon *et al.* 1998, Mackinnon *et al.* 1999, Wagner *et al.* 1997] have also demonstrated that efficient guiding of ultraintense pulses in a channel is indeed possible. From the point of view of the fast ignitor approach to inertial fusion, the occurrence of non-ponderomotive acceleration mechanisms typical of the ultra-intense regime may result in a loss of energy if the stopping range of these electrons is much greater than the typical size of the compressed core of an IFE pellet. It is therefore important to assess the role of these additional acceleration mechanisms and their importance in the energy balance.

Fast electrons generated in laser-plasma interactions at relativistic intensities can be studied directly using electron spectrometers, or indirectly, detecting the gamma-ray bremsstrahlung radiation generated by the interaction of these electrons with matter. The gamma-ray detection technique is particularly suitable when the energy of the fast electrons is expected to be very high ( $\gg 10$  MeV) and usual magnetic electron spectroscopy would require dedicated, large scale equipment.

Here we report on a recent investigation carried out at the Vulcan laser facility, Rutherford Appleton Laboratory (UK) in which gamma-ray detection was employed to study the effect of a precursor channelling pulse on the electron acceleration obtained with the main Vulcan CPA (Chirped Pulse Amplification) laser pulse (75 J, 1 ps, 1.054  $\mu$ m) in an underdense plasma. The electrons were converted via bremsstrahlung into gamma-rays, basically when the beam of accelerated electrons collided with massive components present along its path in the vacuum chamber where the laser plasma interactions took place. The gamma-ray yield was monitored for different conditions of the preformed channel by varying the delay between the channel forming pulse and the main CPA pulse.

## 2. EXPERIMENTAL SET-UP

The layout of the experimental arrangement has been published elsewhere [Galimberti *et al.* 2000]. The plasma was produced by using a well established technique [Gizzi *et al.* 1994] based upon the explosion of thin plastic foils (0.1, 0.3 or 0.5  $\mu\text{m}$  thick) by two 600 ps, 0.527  $\mu\text{m}$  Vulcan laser pulses at a total irradiance of about  $5 \cdot 10^{14} \text{ W/cm}^2$ . After a suitable delay (typically of the order of 1 ns) the main CPA pulse was focused into the plasma. At this time the peak density of the plasma was below  $n_c/10$  and its longitudinal extension was of the order of 1mm. With an  $f/3.5$  focusing optics the irradiance "in vacuum" of the main CPA pulse was up to  $5 \cdot 10^{19} \text{ W/cm}^2$  (about 50 J on target, with up to 50 % of the energy in a 10-15  $\mu\text{m}$  focal spot). A fraction of the energy of the main CPA pulse was used to provide a prepulse, collinear with the main pulse. The prepulse could be focused into the preformed plasma before the main pulse and used to open a density channel. The delay  $\Delta t$  between the channel forming pulse and the main pulse ranged from 20 to 120 ps, in the data set discussed in this paper. A further small fraction of the CPA pulse was frequency quadrupled and used as a transverse optical probe reaching the channel with a fixed delay of 5 ps after the propagation of the main pulse through the plasma. Interferometry was performed with the probe in a modified Nomarsky configuration [Benattar *et al.* 1979]. The relative timing of the four pulses (for heating, channel formation, propagation and probing respectively) is shown in Fig. 1. For the data discussed in this paper, only the channel formation to propagation time  $\Delta t$  was varied. Other diagnostics included calorimetry of the energy transmitted through the plasma, imaging of the transmitted laser spot, forward and back-scatter spectroscopy.

A set of photomultipliers coupled with scintillating crystals (thickness ranging from 12.5 to 50.1 mm) was placed along the direction of the transmitted CPA pulse while two additional 50.1 mm detectors were placed at 45... and 90... respectively. All scintillators were shielded from side-scattered radiation by a 50 mm lead case. Lead slabs were also used to reduce the signal below the PM saturation level. According to numerical simulations performed using the code GEANT4 [GEANT4 1998], the total mass density placed along the line of view of the detectors ensures that primary electrons with energy up to several hundreds of MeV do not reach the detectors. As electrons of such a level of energy are very unlikely to be produced, we can assume that the signal of the scintillators is mostly due to gamma-ray photons generated by bremsstrahlung of primary electrons.

## 3. RESULTS AND DISCUSSION

A preliminary survey [Galimberti *et al.* 2000] of the data indicates that a large number of very high-energy electrons were generated mostly in the forward direction by the CPA laser pulse propagating through the preformed plasma channel. Assuming a given direction of the primary electrons (i.e. the direction of propagation of the main laser pulse), the comparison of simulation with the experimental data obtained from the scintillators allows a correlation to be established between the number of electrons and their energy. The properties of the primary electron beam from which  $\gamma$ -rays originate have been reconstructed using a Monte Carlo simulation code. This simulation indicates that the "mean" energy of individual electrons must be  $>10 \text{ MeV}$  for a large number of electrons (up to a number of the order of  $10^{13}$ ).

A  $\gamma$ -ray signal was also observed when the high intensity CPA pulse directly interacted with the plasma, without any preliminary formation of the channel. In this case, however, the signal was found to be extremely variable shot-to-shot. Correspondingly, the interferograms taken 5 ps after the main pulse propagation, showed clear evidence for laser beam break-up and formation of filaments [Galimberti *et al.* 2000].

Much more reproducible data were obtained in the case of CPA pulse propagation in the preformed channel. They showed an interesting trend of the  $\gamma$ -ray signal to increase when the delay between the channel formation and the arrival of the main pulse on the plasma increased from 20 to 120 ps. In order to better discuss this effect, in this paper we will restrict ourselves to a homogeneous set of data, namely those obtained with targets of 0.3  $\mu\text{m}$  thickness, at the main pulse nominal irradiance of  $3 \cdot 10^{19} \text{ W/cm}^2$ . Excluding  $\Delta t$ , all the other experimental parameters are fixed, including the intensity of all the laser pulses (devoted to the plasma creation and channel formation, respectively), and the delay of the probe pulse (5 ps after the propagation of the main pulse).

The trend of the  $\gamma$ -ray signal is shown in Fig.2, where the total  $\gamma$ -ray energy released to the detectors is plotted versus the prepulse-pulse delay  $\Delta t$ , for 14 homogeneous events performed with 0.3  $\mu\text{m}$  plastic targets, in the fixed experimental conditions stated above. There is a factor of 4 of increase of the  $\gamma$ -ray yield when the delay between the plasma formation and the main pulse arrival goes from 20 to 120 ps. Correspondingly, the transmission rate of the main pulse after propagation through the channel increases more than six times [Borghesi *et al.* 2001].

As described in the previous Section, simultaneous interferograms have been produced to monitor plasma channeling and the modifications induced on the preformed plasma density by the CPA interaction pulse. In Fig. 3 three of those interferograms are

shown, corresponding to the three  $\gamma$ -ray data indicated by empty circles in Fig. 2. The three interferograms were obtained for three different delays  $\Delta t$ , but the same delay from the plasma formation time. They represent, then, the fringe pattern produced by: i) the channel evolution, ii) the propagation of the main pulse. Referring to the interferograms of Fig. 3, the laser pulses come from the left hand side. The Nomarsky technique we have used allows to investigate both the entrance and exit sides of the original target.

The first interferogram (top picture of Fig. 3) shows the pattern for  $\Delta t = 30$  ps. Qualitatively, there is evidence that, though the channel is already well defined, important fringe perturbations are present inside the channel, particularly in the higher density region close to the original target position. There is also evidence that the prepulse forming the channel exhausts its energy content while propagating through the plasma (consistently, the transmission of the prepulse energy through the plasma is practically zero). The energy transferred to the ions in the Coulomb explosion process [Borghesi *et al.* 1998] is therefore smaller in the higher density region close to the original target position than in the low density entrance plasma. This determines a less efficient, slower expansion and the presence of turbulent structure in the early stages of the channel expansion. As a matter of fact, in shots where only the preforming channel pulse is present, no evidence of channel formation at the back side of the target was collected. For 30 ps delay, the transmission rate is still low (13% in our case), though definitely higher than the transmission for  $\Delta t = 20$  ps (6% [Borghesi *et al.* 2001]). There is little evidence for the pulse transmission in the exit portion of the channel (right hand side of the interferogram). Another important feature is the fringe blurring at the channel boundary, which is likely to be a combined effect of the fast channel expansion and of refraction due to the steep density gradients.

The second interferogram (middle picture of Fig. 3) shows the pattern for  $\Delta t = 60$  ps. The channel has a larger diameter, but is still expanding (fringe blurring). The channel entrance is less perturbed, but there is a clear evidence of filamentary and rather chaotic structures at the exit from the channel. Also in this case there is an analogy with observation performed after direct irradiation of the plasma by the main pulse [Galimberti *et al.* 2000, Borghesi *et al.* 2001]. Our interpretation is that, although the channel appears considerably more homogeneous than in the previous case, the channel is well developed only in the front region of the plasma. The main pulse is then guided up to the central region of the plasma, where it has to dig its own channel, spending a considerable fraction of its energy and undergoing beam break-up and filamentation. Correspondingly, the transmission increases to 19%.

The third interferogram (bottom picture of Fig. 3) shows the pattern for  $\Delta t = 120$  ps. Fringe blurring at the channel boundary is no longer present, indicating a channel in a quasi-stationary state. The transmission reaches about 38%. The channel region shows a quite regular fringe pattern. The rear side portion of the fringe pattern was lost in this shot.

A more quantitative study of the channel evolution has been done by analysing the interferograms with a novel numerical tool (IACRE) which makes an extensive use of the Continuous Wavelet Transforms [Tomassini *et al.* 2001]. This technique is much more powerful than the standard FFT-based one in two main aspects: it is *more robust* since it can be successfully used in analysing poor-quality interferograms and *more accurate* since its sensibility in the phase-shift estimation is higher than the one of the FFT-based method. In particular the IACRE technique was proved to be very effective in evidencing and studying small scale perturbations.

With this technique the phase-shift maps of suitable portions of the two interferograms of Fig. 3 are obtained. They are then (whenever it is possible) symmetrised respect to the axis with an algorithm which optimises the matching between the two half-maps. Finally, density maps are computed via Abel inversion. However, in some regions the fringe deviation from symmetry is so large that symmetrisation is not justified.

The IACRE method has been applied to the fringe patterns obtained for  $\Delta t = 30$  and 120 ps (top and bottom of picture of Fig. 3, respectively). In the case of  $\Delta t = 120$  ps, the level of symmetry was quite high, allowing to produce a density map of the whole channel region in front of the target, which appears in the top-left picture of Fig. 4. The channel density profiles appear regular and smooth both longitudinally, along the axis (bottom left of Fig. 4) and transversally. The transverse profile is shown at two different positions along the channel, at the entrance ( $x = -450$  m, picture top right of Fig. 4) and closer to the original target position ( $x = -100$  m, picture bottom right of Fig. 4). In Fig. 4 and Fig. 5  $x = 0$  approximately corresponds to the original target position.

In the case of  $\Delta t = 30$  ps, the level of symmetry was acceptable only at the entrance of the channel. The density map obtained in that region is shown in the top-left picture of Fig. 5. At the bottom of the same figure, longitudinal on-axis and transverse (at  $x = -450$  m) line-outs of the same region are shown. In the remainder of the interferogram, the phase shift map evidenced a filamentary and rather chaotic structure, as proved by the transversal line-out of the phase shift taken at  $x = -100$  m (top right of Fig. 5). At this time after the channel formation, the channel density profile appears to be unsuitable for the main pulse propagation a few hundred micrometers from its entrance.

The interpretation and analysis of the data are presently in progress. Eventually, computational modelling of the laser propagation in the plasma conditions corresponding to the various channelling-propagation delays will be required. However from this preliminary survey of the data it appears clear that the presence of the channel determines a clear transition from a chaotic and unstable acceleration regime, dominated by filamentation and laser beam break-up [Wang *et al.* 2000, Young & Bolton 1996], to more controllable experimental conditions. The efficiency of the acceleration process increases as the channel interior becomes smoother, and the main pulse propagates in an uniform low-density plasma with gently rising edges.

In conclusion, the comparative analysis of gamma-ray yield and interferograms, performed on an homogeneous set of data, shows that the technique used to pre-form a density channel in the plasma may be effective to accelerate electrons with a very intense laser pulses of 1 ps duration. As a matter of fact, a large number of electrons were found to be accelerated forward to ultra-relativistic energies. However the status of evolution of the channel seems to play a major role in the efficiency of the acceleration process. In the experimental conditions of the data we have studied, the energy collected by the gamma-ray detectors, which is proportional to the sum of the individual electron energies, increased with the delay between the channel forming pulse and the accelerating pulse. Though longer delays were not investigated, a delay of the order of 100-120 ps gave evidence for efficient acceleration corresponding to a rather stationary status of the channel in the time scale of the accelerating pulse propagation (a few picoseconds). The interferograms also suggest that for the given plasma parameters, a channel was fully formed only on the front side of the plasma. This is obviously detrimental to an efficient propagation of the accelerating pulse.

We would like to thank the staff of the Central Laser Facility at RAL for their enthusiastic support in preparing and carrying out the experiment. We also thank A. Barbini (IFAM-CNR) for his contribution to the experimental set up. One of the authors (P.T.) acknowledges financial support from M.U.R.S.T. (Project: "Metodologie e diagnostiche per materiali e ambiente"). The experiment was funded by an ESPRC grant.

#### 4. REFERENCES

- AMIRANOFF F. *et al.* 1998 Phys. Rev.Lett. **81**, 995  
BENATTAR R., POPOVICS C. and SIEGEL R. 1979 Rev.Sci.Instrum. **50**,1583  
BORGHESI M. *et al.* 1997 Phys. Rev. Lett. **78**, 879  
BORGHESI M. *et al.* 1998 Phys. Rev. Lett. **80**, 5137  
BORGHESI M. *et al.* 1999 Phys. Rev. Lett. **83**, 4309  
BORGHESI M. *et al.* 2000 Laser and Particle Beams **18**, 1  
BORGHESI M. *et al.* 2001 **RAL-TR-2000-034** Rutherford Appleton Laboratory  
COWAN T.E. *et al.* 2000 Phys. Rev. Lett. **84**, 903  
ESAREY E. *et al.* 1998 Phys. Rev. Lett., **80**, 555  
GALIMBERTI M. *et al.* 2000 XXVI Eclim Conference, SPIE Proceedings  
GEANT4: LCB Status Report/**RD44**, CERN/LHCC-98-44, (1998)  
GIZZI L.A. *et al.* 1994 Phys. Rev. E **49**, 5628  
GREMILLET L. *et al.* 1999 Phys. Rev. Lett. **83**, 5015  
KRUSHELNICK K. *et al.* 1997 Phys. Rev. Lett. **78**, 4047  
KRUSHELNICK K. *et al.* 1999 Phys. Rev. Lett. **83**, 737  
LEDINGHAM K.W.D. *et al.* 2000 Phys. Rev. Lett. **84**, 899  
LEEMANS W.P. *et al.* 1998 Phys. Plasmas. **5**, 1615  
MALKA V. *et al.* 1997 Phys. Rev. Lett., **79**, 2979  
MACKINNON A.J. *et al.* 1998 Phys. Rev. Lett. **80**, 5349  
MACKINNON A.J. *et al.* 1999 Phys. of Plasmas **6**, 2185  
PUKHOV A. *et al.* 1999 Phys. Plasma **6**, 2847  
TAJIMA T. & DAWSON J.M. 1979 Phys. Rev. Lett. **74**, 267  
TOMASSINI P. *et al.* 2001 submitted to Applied Optics  
TZENG K.C. *et al.* 1997 Phys. Rev. Lett. **79**, 5258  
YOUNG P.E. & BOLTON P.R. 1996 Phys. Rev. Lett. **77**, 4556  
WAGNER R. *et al.* 1997 Phys. Rev. Lett. **78**, 3125  
WANG X. *et al.* 2000 Phys. Rev. Lett. **84**, 5324

Figure 1 - Timing of the four laser pulses involved in the experiment. Pulse shapes and delays are not in scale.

Figure 2. Energy released by the gamma-ray photons to the detector set versus the delay  $\Delta t$  between the channel forming pulse and the main CPA pulse. The data were obtained with 0.3 plastic targets, and timing as indicated in Fig 1. The nominal irradiance of the main CPA pulse was  $3 \cdot 10^{19} \text{ W/cm}^2$ .

Figure 3. Interferograms obtained (with 0.3 m plastic targets, and timing as indicated in Fig 1) by ultraviolet transversal probing of the channel, 5 ps after the propagation of the main pulse. Top:  $\Delta t = 30 \text{ ps}$ , transmission 13%. Middle:  $\Delta t = 60 \text{ ps}$ , transmission 19%. Bottom:  $\Delta t = 120 \text{ ps}$ , transmission 38%.

Figure 4. Electron density distribution in the channel region inferred from the interferogram  $\Delta t = 120 \text{ ps}$  (bottom of Fig. 3). The density is calculated relative to the background density surrounding the channel for a given value of the x coordinate. Top-left: the symmetrised density map; notice that the z-axis scale is expanded respect to the x-axis one. Bottom-left: longitudinal line-out of the density along the channel axis. Top-right: transversal line-out of the density taken at  $x = -100 \text{ m}$ . Bottom-right: transversal line-out of the density taken at  $x = -450 \text{ m}$ .  $x = 0$  approximately corresponds to the original target position.

Figure 5. Numerical analysis of the channel region inferred from the interferogram  $\Delta t = 30 \text{ ps}$  (top of Fig. 3). Top-left: the symmetrised electron density map of the entrance region, after subtraction of the background density. Bottom-left: longitudinal line-out of the density along the channel axis. Top-right: transversal line-out of the density taken at  $x = -100 \text{ m}$ . Bottom-right: transversal line-out of the phase-shift taken at  $x = -450 \text{ m}$ .  $x = 0$  approximately corresponds to the original target position.











